

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
18 September 2003 (18.09.2003)


PCT

(10) International Publication Number  
WO 03/076986 A1

- (51) International Patent Classification<sup>7</sup>: G02B 6/00, 6/35, 6/26
- (74) Agent: VAN DEN HOOVEN, Jan; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (21) International Application Number: PCT/TB03/00470
- (22) International Filing Date: 7 February 2003 (07.02.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 02075932.0 8 March 2002 (08.03.2002) EP
- (71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): CREEMERS, Tijsbert, M. H. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published: — with international search report

[Continued on next page]

(54) Title: DISPLAY DEVICE COMPRISING A LIGHT GUIDE



(57) Abstract: A display device comprises row (5) and column (6) electrodes provided on a front plate and a light guide, a moveable element (3) provided with a common electrode (7), and means (17) for supplying voltages to the electrodes. A controllable image element is thereby formed on a crossing of the row and column electrodes. In dependence on driving pulses received by the electrodes, the moveable element can be set either to the front plate or the back plate. At one side of the light guide, light generated by a light source is coupled into the light guide. When the moveable element is in contact with the light guide, light is coupled out of the light guide at that location. Collimating means situated between the light source and the light guide improve the uniformity of the display device.



WO 03/076986 A1